

Test Report

No. TRPVP07062/20P/02

Commission Testing
according to IEC / EN 61215-2

Applicant: **Sunrise energy Co., Ltd.**
No.20 Tongzi River West Road, Zhonglou Development Zone,
Changzhou Jiangsu, 213023 P.R. China

File No.: PVP07062/20P-02

Designed: *Nov. 16. 2020* by: 

Reviewed: *Nov. 17. 2020* by: *Bella Cm*

All copyright and joint copyrights with respect to studies, assessments, test results, calculations, presentations, etc., drafted by TÜV NORD (Hangzhou) Co., Ltd. shall remain the property of TÜV NORD (Hangzhou) Co., Ltd. TÜV NORD (Hangzhou)'s contractual partner may use assessments, studies, test results, calculations, presentations, etc., drafted within the scope of the contract only for the purpose agreed in the contract or agreement. It is not permissible to pass on to third parties the reports, assessments, test results, calculations, presentations, etc., drawn up by TÜV NORD (Hangzhou) Co., Ltd. or to publish them in abridged form, unless the parties to the contract have concluded a written agreement on the passing on, presentation or publication of extracts from them.

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

Applicant	Sunrise energy Co., Ltd. No.20 Tongzi River West Road, Zhonglou Development Zone, Changzhou Jiangsu, 213023 P.R. China
Manufacturer	Sunrise energy Co., Ltd. No.20 Tongzi River West Road, Zhonglou Development Zone, Changzhou Jiangsu, 213023 P.R. China
Order No.	QT-PVP07062/20P_R1
Date of Application	09/16/2020
Product	Crystalline Silicon Photovoltaic Modules
Module type(s)	PV Modules with 6" Half-cut Mono-crystalline Silicon Solar Cells: 144 cells: SR-M672430HLP
General Information	
• Maximum System Voltage.... :	DC 1500V
• Electrical Protection Class.... :	Class II
• Fire Safety Class	N/A
Type of examination	Commission testing only
Testing Period	09/07/2020 - 11/02/2020
Testing Laboratory.....	TÜV Nord PV Science and Technology Co., Ltd. 2/F., Building 4, No. 880, Ziyue Road, Minhang District, Shanghai, China

Test results listed in this test report refer exclusively to the mentioned test sample.

Partly copying is not permitted without explicit agreement of the owner.

The submitted test samples as described in the reports hereunder are based on the requirements:
IEC 61215-2:2016 / EN 61215-2:2017 + AC:2017 + AC:2018 "Terrestrial photovoltaic (PV) modules - Design qualification and type approval - Part 2: Test procedures"

List of contents

List of contents.....	3
Summary of testing.....	4
General remarks.....	5
General product information	6
Module type: SR-M672430HLP	6
Module group assignment.....	7
Module type: SR-M672430HLP	7
Test result overview.....	8
Module type: SR-M672430HLP	8
Test results of IEC / EN 61215-2.....	9
Module type: SR-M672430HLP	9
4.1 Visual inspection (initial) - MQT01	9
4.3 Insulation test (initial) - MQT03.....	11
4.15 Wet leakage current test (initial) - MQT15	12
4.13 Damp heat 1000 test - MQT13	13
Annex 1: List of measurement equipment.....	16
Annex 2: Statement of the estimated uncertainty of the test results.....	17
Annex 3: Photos	18
Module type: SR-M672430HLP	18
Annex 4: Photos of insulation tape.....	20

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

Summary of testing

According to the enquiry of the applicant, a commission test was performed according to IEC 61215-2:2016.

Test items see page 7 for details.

Module type SR-M672430HLP was delivered to lab and was conducted with all the related tests.

All tests were successfully completed.

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

General remarks

Test item particulars:	
Accessories and detachable parts included in the evaluation	N/A
Options included	N/A
Abbreviations used in the report:	
HF - Humidity Freeze	TC - Temperature Cycling
DH - Damp Heat	Vmpp - Maximum power voltage
Impp - Maximum power current	Voc - Open circuit voltage
Isc - Short circuit current	FF - Fill Factor
Pmpp - Maximum power	α - Current temperature coefficient
NMOT - Nominal Module Operating Temperature	β - Voltage temperature coefficient
STC - Standard Test Conditions	γ - Power temperature coefficient
CTI - Comparative Tracking Index	PTI - Proof Tracking Index
RTI - Relative Temperature Index	RTE - Relative Thermal Endurance index
TI - Temperature Index	DTI - Distance through insulation
CI - Clearances	Cr - Creepage distances
PD - Pollution Degree	MG - Material Groups
Possible test case verdicts:	
Test case does not apply to the test object	Not Applicable (N/A)
Test object does meet the requirement	Pass (P)
Test object does not meet the requirement	Fail (F)
Other remarks:	
The test verdicts presented in this report relate only to the object tested. This report shall not be reproduced except in full, without the written approval of the issuing testing laboratory. “(see Annex #)” refers to additional information appended to the report. “(see Table #)” refers to a table appended to the report. Power degradation data expressed in negative value indicates a reduction of maximum power output. Power degradation data expressed in positive value indicates an increment of maximum power output. Throughout this report, a point is used as the decimal separator.	

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

General product information

Module type: SR-M672430HLP

Product Electrical Ratings at STC:	
Nominal maximum power (Pmax) [W] with tolerance	430 (0 ~ +3%)
Nominal open circuit voltage at (Voc) [V] with tolerance ...:	49.22 ±3%
Nominal maximum power voltage (Vmpp) [V]	40.59
Nominal short circuit current at (Isc) [A] with tolerance	11.21 ±3%
Nominal maximum power current (Impp) [A]	10.60
Product Safety Ratings:	
Maximum system voltage [V]	1500
Fuse rating [A]	20
Safety class in accordance with IEC 61140	Class II
Fire safety class	N/A
Recommended maximum series module configurations ..:	N/A
Recommended maximum parallel module configurations :	N/A

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

Module group assignment

Module type: SR-M672430HLP

Sample #	Serial number	Dimension (l x w x h) [mm]	Remark
1	H72MMA20071610014	2115 x 1052 x 40	DH1000

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

Test result overview

Module type: SR-M672430HLP

Initial examinations			-
MQT01	Visual inspection	See table 4.1	P
MQT03	Insulation test.....	See table 4.3	P
MQT15	Wet leakage current test.....	See table 4.15	P
MQT02	Maximum power determination.....	See table 4.2	P

Sample 1#			-
MQT13	Damp heat test (1000h).....	See table 4.13	P

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

IEC / EN 61215-2			
Clause	Requirement + Test	Result - Remark	Verdict

Test results of IEC / EN 61215-2

Module type: SR-M672430HLP

4.1 Visual inspection (initial) - MQT01		-
Test date [MM/DD/YYYY].....:	09/07/2020	-
Sample #	Nature and position of initial findings - comments or attach photos	-
1	No visual defects	P
Supplementary information: N/A		

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

IEC / EN 61215-2							
Clause	Requirement + Test		Result - Remark				Verdict
4.2 Maximum power determination (initial) - MQT02							-
Test date [MM/DD/YYYY].....:			09/07/2020				-
Ambient temperature [°C].....:			Corrected to 25.0				-
Irradiance [W/m²].....:			Corrected to 1000				-
Sample #	Voc [V]	Vmp [V]	Isc [A]	Imp [A]	Pmp [W]	FF [%]	-
1	49.02	41.47	10.74	10.28	426.3	80.97	-
Supplementary information: N/A							

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

IEC / EN 61215-2				
Clause	Requirement + Test	Result - Remark		Verdict
4.3 Insulation test (initial) - MQT03				-
Test date [MM/DD/YYYY].....:		09/07/2020		-
Test voltage applied [V].....:		2 minutes of 1500 and 1 minute of 4000		-
Sample #	Required [MΩ]	Measured [MΩ]	Dielectric breakdown?	-
1	18.0	>1000	No	P
Supplementary information: Minimum requirement according to the standard is 40MΩ·m². Area of the module is 2.22m².				

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

IEC / EN 61215-2			
Clause	Requirement + Test	Result - Remark	Verdict
4.15 Wet leakage current test (initial) - MQT15			-
Test date [MM/DD/YYYY].....:		09/07/2020	-
Test voltage applied [V].....:		2 minutes of 1500	-
Solution resistivity [Ω/cm] / <3500		1977	-
Solution temperature [$^{\circ}\text{C}$] / 22 $\pm$ 2		21.9	-
Sample #	Required [$\text{M}\Omega$]	Measured [$\text{M}\Omega$]	-
1	18.0	>1000	P
Supplementary information: Minimum requirement according to the standard is $40\text{M}\Omega\cdot\text{m}^2$. Area of the module is 2.22m^2 .			

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

IEC / EN 61215-2							
Clause	Requirement + Test			Result - Remark			Verdict
4.13 Damp heat 1000 test - MQT13							-
Sample #		1					-
Test date [MM/DD/YYYY] / start - end...		09/11/2020 - 11/02/2020					-
Total hours [hours]		1000					-
Supplementary information: N/A							
4.1 Visual inspection (after damp heat 1000 test) - MQT01							-
Test date [MM/DD/YYYY].....		11/02/2020					-
Sample #	Nature and position of initial findings - comments or attach photos						-
1	No visual defects						P
Supplementary information: N/A							
4.2 Maximum power determination (after damp heat 1000 test) - MQT02							-
Test date [MM/DD/YYYY].....		11/02/2020					-
Ambient temperature [°C].....		Corrected to 25.0					-
Irradiance [W/m²].....		Corrected to 1000					-
Sample #	Voc [V]	Vmp [V]	Isc [A]	Imp [A]	Pmp [W]	FF [%]	-
1	48.86	41.12	10.60	10.13	416.5	80.39	-
Supplementary information: N/A							
4.3 Insulation test (after damp heat 1000 test) - MQT03							-
Test date [MM/DD/YYYY].....		11/02/2020					-
Test voltage applied [V].....		2 minutes of 1500 and 1 minute of 4000					-
Sample #	Required [MΩ]		Measured [MΩ]		Dielectric breakdown?		-
1	18.0		>1000		No		P
Supplementary information: Minimum requirement according to the standard is 40MΩ·m². Area of the module is 2.22m².							

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

IEC / EN 61215-2			
Clause	Requirement + Test	Result - Remark	Verdict
4.15 Wet leakage current test (after damp heat 1000 test) - MQT15			-
Test date [MM/DD/YYYY].....:	11/02/2020		-
Test voltage applied [V].....:	2 minutes of 1500		-
Solution resistivity [Ω/cm] / <3500	2016		-
Solution temperature [$^{\circ}\text{C}$] / 22 $\pm$ 2	22.4		-
Sample #	Required [$\text{M}\Omega$]	Measured [$\text{M}\Omega$]	-
1	18.0	>1000	P
Supplementary information: Minimum requirement according to the standard is $40\text{M}\Omega\cdot\text{m}^2$. Area of the module is 2.22m^2 .			

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

IEC / EN 61215-2			
Clause	Requirement + Test	Result - Remark	Verdict

Power degradation of each module after each test sequences						-
Sample #	Pmp (initial) [W]	Pmp (final) [W]	Reproducibility r [%]	Power degradation [%]	Maximum allowed degradation [%]	-
1	426.3	416.5	0.00	-2.30	-5.00	P
Supplementary information: Maximum allowed degradation [%] = $-(5 + 0.95 \times r)$						

Test Report



File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

Annex 1: List of measurement equipment

Measurement / testing	Measuring equipment	Equipment ID	Calibration due date
Visual inspection	Luminometer	TNRDTO002	12/18/2020
Maximum power determination	Pulsed Solar Simulator	TNRDEQ001	11/06/2020
Insulation test	Withstanding voltage/Insulation resistance tester	TNRDTI020	09/28/2021
Damp heat test	High and low temperature chamber	TNRDEQ006	11/04/2020
Wet leakage current test	Withstanding voltage/Insulation resistance tester	TNRDTI020	09/28/2021
	Conductive meter	TNRDTI004	12/16/2020

File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

Annex 2: Statement of the estimated uncertainty of the test results

The total measuring uncertainty of P_{mpp} is $\leq 2.68\%$

The total measuring uncertainty of I_{sc} is $\leq 2.12\%$

The total measuring uncertainty of V_{oc} is $\leq 0.82\%$


Test Report

File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

Annex 3: Photos

Module type: SR-M672430HLP




Front overview



Back overview




Label



Solar cell



Frame



Grounding Mark

Test Report

File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02




Junction box (FT20xv)



Junction box (opened)

N/A



Bypass diode (Junction box is potted)

Cable (H1Z2Z2-K 1x4.0mm²)



Mark (Do not disconnect under load)




Connectors (not specified)

Test Report


File No.: PVP07062/20P-02

Test Report No.: TRPVP07062/20P/02

Annex 4: Photos of insulation tape



Sample #1



Sample #1

----- End of test report -----